

SAFETY DATA SHEET **AUTOFLEX** Optimizer (PART C)

1) Identification

Product identifier

Tradename: AutoFlex Gloss Optimizer (Part C)

Article number: AFX-OPT (Part C)

Application of the substance / the mixture Coating

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

AutoFlex Coatings
2103 Park Central Blvd
Pompano Beach, FL 33064
Phone: 605-610-8861

Information department: 605-610-8861

Emergency telephone number: CHEMTREC 1-800-424-9300

2) Hazards Identification

Classification of the substance or mixture



GHS02 Flame

Flammable Liquids - Category 2

H225 Highly flammable liquid and vapour.



GHS08 Health hazard

Reproductive Toxicity - Category 1A

H360 May damage fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure - Category 2

H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Eye Irritation - Category 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure - Category 3 H336 May cause drowsiness or dizziness.

Label elements

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



GHS02



GHS07



GHS08

Signal word Danger

Hazard-determining components of labeling:

benzyl butyl phthalate
butanone
toluene

n-butyl acetate

Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H360 May damage fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P242 Use non-sparking tools.

P243 Take actions to prevent static discharges.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.

P314 Get medical advice/attention if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

NFPA ratings (scale 0 - 4)



Health = 2
Fire = 3
Reactivity = 0

HMIS-ratings (scale 0 - 4)

HEALTH	*2
FIRE	3
REACTIVITY	0

Health = *2
Fire = 3
Reactivity = 0

3) Composition/Information on Ingredients

Chemical characterization: Mixtures

Description:

Mixture: consisting of the following components.

Weight percentages

Dangerous components:

78-93-3 butanone

10-30% w/w *

85-68-7 benzyl butyl phthalate

≥10-≤13% w/w *

108-88-3 toluene

≥5-<10% w/w *

123-86-4 n-butyl acetate

≥5-<10% w/w *

108-65-6 2-methoxy-1-methylethyl acetate

1-5% w/w *

* Actual concentration ranges are withheld as a trade secret.

4) First Aid Measures

Description of first aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Generally the product does not irritate the skin.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: If symptoms persist consult doctor.

Information for doctor:

Most important symptoms and effects, both acute and delayed No further relevant information available.

Indication of any immediate medical attention and special treatment needed No further relevant information available.

5) Firefighting Measures

Extinguishing media

Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

Special hazards arising from the substance or mixture No further relevant information available.

Advice for firefighters

Protective equipment: No special measures required.

6) Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions: Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7) Handling and Storage

Handling:

Precautions for safe handling No special measures required.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility: Not required.

Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Specific end use(s) No further relevant information available.

8) Exposure Controls / Personal Protection

Additional information about design of technical systems: No further data; see item 7.

Control parameters

Components with limit values that require monitoring at the workplace:

78-93-3 butanone

EL Short-term value: 100 ppm

Long-term value: 50 ppm

EV Short-term value: 885 mg/m³, 300 ppm

Long-term value: 590 mg/m³, 200 ppm

108-88-3 toluene

EL Long-term value: 20 ppm

R

EV Long-term value: 20 ppm

123-86-4 n-butyl acetate

EL Long-term value: 20 ppm

EV Short-term value: 950 mg/m³, 200 ppm

Long-term value: 710 mg/m³, 150 ppm

108-65-6 2-methoxy-1-methylethyl acetate

EL Short-term value: 75 ppm

Long-term value: 50 ppm

EV Long-term value: 270 mg/m³, 50 ppm

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eyeprotection:



Tightly sealed goggles

9) Physical and Chemical Properties

Information on basic physical and chemical properties

General Information

Appearance:

Form:	Liquid
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.

Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	79-80.5 °C

Flash point: -4 °C

Flammability (solid, gaseous): Not applicable.

Ignition temperature: 370 °C

Decomposition temperature: Not determined.

Auto igniting: Product is not selfigniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Explosion limits:

Lower:	0.4 Vol %
Upper:	13 Vol %

Vapor pressure at 20 °C: 233 hPa

Density at 20 °C: 1.00092 g/cm³

Relative density: Not determined.

Vapor density: Not determined.

Evaporation rate: Not determined.

Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

Partition coefficient (n-octanol/water): Not determined.

Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

Solvent content:

Organic solvents:	41.8 %
VOC content:	41.84 %
	418.8 g/l / 3.50 lb/gal

Solids content: 58.2 %

Other information: No further relevant information available.

I 0) Stability and Reactivity

Reactivity No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: No dangerous decomposition products known.

I 1) Toxicological Information

Information on toxicological effects

Acute toxicity:

LD/LC50 values that are relevant for classification:

108-88-3 toluene

Oral LD50 5,000 mg/kg (rat)

Dermal LD50 12,124 mg/kg (rabbit)

Inhalative LC50/4 h 5,320 mg/l (mouse)

Primary irritant effect:

on the skin: No irritant effect.

on the eye: Irritating effect.

Sensitization: No sensitizing effects known.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

Carcinogenic categories

IARC(International Agency for Research on Cancer)

85-68-7 benzyl butyl phthalate: 3

108-88-3 toluene: 3

NTP (National Toxicology Program)

None of the ingredients is listed.

I 2) Ecological Information

Toxicity

Aquatic toxicity: No further relevant information available.

Persistence and degradability No further relevant information available.

Behavior in environmental systems:

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects No further relevant information available.

I 3) Disposal Considerations

Waste treatment methods

Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

I 4) Transport Information

UN-Number

DOT, TDG, IMDG, IATA

UN proper shipping name

DOT

TDG

UN1263

Paint

1263 Paint, MARINE POLLUTANT/ENVIRONMENTALLY
HAZARDOUS, special provision 640D

PAINT

IMDG, IATA

Transport hazard class(es)

DOT




Class

Label

TDG, IMDG

3 Flammable liquids

3



Class

Label

3 Flammable liquids

3

IATA



Class

Label

Packing group

DOT, TDG, IMDG, IATA

Environmental hazards:

3 Flammable liquids

3

II

Product contains environmentally hazardous substances: benzyl
butyl phthalate

Yes

Symbol (fish and tree)

Symbol (fish and tree)

Warning: Flammable liquids

F-E, S-E

B

Marine pollutant:

Special marking (TDG):

Special precautions for user

EMS Number:

Stowage Category

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

Transport/Additional information:

DOT

Quantity limitations

On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L

TDG

Excepted quantities (EQ)

Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

IMDG

Limited quantities (LQ)

Excepted quantities (EQ)

5L
Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

UN "Model Regulation":

UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS

I 5) Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Sara

Section 355 (extremely hazardous substances):

None of the ingredient is listed.

Section 313 (Specific toxic chemical listings):

78-93-3 butanone

108-88-3 toluene

TSCA (Toxic Substances Control Act):

78-93-3 butanone

85-68-7 benzyl butyl phthalate

16883-83-3 benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate

108-88-3 toluene

123-86-4 n-butyl acetate

108-65-6 2-methoxy-1-methylethyl acetate

Canadian substance listings:

Canadian Domestic Substances List (DSL)

78-93-3 butanone

85-68-7 benzyl butyl phthalate

16883-83-3 benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate

108-88-3 toluene

123-86-4 n-butyl acetate

108-65-6 2-methoxy-1-methylethyl acetate

Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

Canadian Ingredient Disclosure list (limit 1%)

78-93-3 butanone

85-68-7 benzyl butyl phthalate

108-88-3 toluene

123-86-4 n-butyl acetate

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



GHS02

GHS07

GHS08

Signal word Danger

Hazard-determining components of labeling:

benzyl butyl phthalate

butanone

toluene

n-butyl acetate

Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H360 May damage fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P242 Use non-sparking tools.

P243 Take actions to prevent static discharges.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.

P314 Get medical advice/attention if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16) Other Information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: Environment protection department.

Contact: (901) 363-4955

Date of preparation / last revision 01/1/2019

Abbreviations and acronyms:

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO) IMDG:

International Maritime Code for Dangerous Goods

DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative

* **Data compared to the previous version altered.**